

CC-Dr. Schutz GmbH

Manufacture and Distribution of high-quality floor cleaning and care products, as well as cleaning systems

Development · Production · Logistics

CC-Dr. Schutz GmbH
Steinbrinksweg 30
D-31840 Hessisch Oldendorf

Tel: +49-(0)51 52-97 79-0
Fax: +49-(0)51 52-97 79-30

info@dr-schutz.com · www.dr-schutz.com

Product-Information

ScratchFix PU Repair Pen

1. Product description

Special PU pen for filling individual scratches on resilient floor coverings. Good adhesive qualities. Extramatt visual effect. Quick drying. Easy to apply.

2. Areas of application

Resilient floor coverings, either factory-coated PU-/PUR, or treated with a PU sealer.

3. Application

Before use, the floor covering must be carefully cleaned, so that it is free of any dirt or grease. First, work on erasing deeper scratches with the plastic wedge, at right angles to the crater, so that any excess is removed. Then even out the surface along the scratch with the grey abrasive fleece. Remove the resulting fine dust with a light, moist cloth.

(Before first use, rinse the tip of the brush out under water and dry it with a cotton towel)
Before using, shake the pen vigorously for about 15 seconds, and after removing the cap, de-aerate, i.e. release air. To de-aerate, hold the pen with the tip upwards and push the "PRESS" button and let air escape. After this, point the tip downwards and push the "PRESS" button again and let some drops fall onto a cloth. Now the brush tip is prepared, guide it carefully along the scratch, dabbing lightly. After drying (about 10 -15 minutes) erase any differences in gloss with the plastic wedge, working at right angles to the scratch.

After use, rinse the brush tip with water and dry it off.

We recommend that all scratches should later be treated with P U Repair Spray in addition (see product information PU Repair Spray). Using the grey abrasive fleece, any differences in the degree of gloss can be evened out. In this case, put a matt finish on the completely dried lacquer (after about 45 – 60 mins.) in the direction of the grain. For partial repairs, it is possible that apparent differences to the remaining area may become visible (e.g. differences in the degree of gloss). This can only be remedied by renovating the entire area (e.g. with P U Sealer). Very deep scratches (in the used surface) can never be completely removed.

4. Technical Data

Gloss grade: extramatt = 6 – 8 GE (60°-measurement)

Best before: use within a minimum of 24 months (sealed in the original container)

Dust-dry: after about 1 - 2 minutes (depending on room & climatic conditions)

Can be walked on: after about 6 hours



Later sealing: possible to apply a coat of PU Sealer over previous basic renovation.

Keep the container closed and out of the reach of children.

5. Container sizes

11 mL - Pen

The information above is given to the best of our knowledge and according to the latest state of technology. Therefore, if the procedural recommendations are carefully followed, as well as our advice regarding the materials, specifically for these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility and this does not release you from an obligation to check our products on delivery to ensure that they are suitable for the purpose and procedures intended. Our notes and advice are therefore not legally binding and cannot be used against us as grounds for liability – which also includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.

